

LC 6000

Specification sheet

SCION 6410 UV DETECTOR

Dimensions & Weights

Dimensions:	490W x 360D x 174H (mm)
Weight :	14 kg
Power Supply:	DC 24 V, 2.5 A (max)/ 60 W
Communication:	Controller Area Network (CAN)

Optical System

Double Beam

Light Source:	D2 Lamp
Wavelength Range:	190nm to 600nm
Spectrum Bandwidth:	8nm
Wavelength Accuracy:	±2nm
Acquisition Rate:	0.5, 1, 10, 20Hz

Parameters

Temperature Range:	4°C to 35°C (no condensation)
Humidity Range:	25% to 85% (no condensation)
Noise Level:	<1 x 10 ⁻⁵
Drift:	<2.5 x10 ⁻⁵
Autozero range:	0.2 to 2 AU
Offset:	0 to 2 AU, 0.001 step
Flow Cell Capacity:	14µL
Flow Cell Pressure Resistance:	14.7MPa (without inlet/outlet tube)
Time Programme:	Maximum 600 min in steps of 0.1 m Maximum number of steps: 50



Programmable Measurements

Wavelength measurements

Baseline Process (only for single wavelength measurements)

Leak Sensor

For the detection of leaks

SCION Instruments HQ
Suite 34, Livingston Business Centre
Kirkton Road South, Livingston,
EH54 7FA, Scotland, UK.
Tel: +44 1506 300 200
sales-eu@scioninstruments.com
www.scioninstruments.com

SCION Instruments NL BV
Amundsenweg 22-24,
4462 GP Goes,
The Netherlands
Tel: +31 (0) 113-287 600
sales-eu@scioninstruments.com
www.scioninstruments.com